

# Corrugated Ramp Cleat

## Specifications



NATURAL RUBBER



RECLAIMED RUBBER



RECYCLED RUBBER



SYNTHETIC RUBBER

March 2010

**Material:** 100% SBR

**Width:** 36 inch

**Length:** 50ft rolls, Custom lengths up to 50 continuous feet are available upon request.

**Thickness:** 3mm or 0.12 inches (just under 1/8 inch)

**Weight:** 0.9 lbs per square foot

**Hardness:** 60 Shore A Nominal

**Compression:** 36% @ 50 PSI

**Tensile Strength:** 600 PSI

**Available Colors:** Black

**Applications:** Access Ramps, Alleys, Boats, Boat Ramps, Churches, Car Restoration, Docks, Duckboards, Entryways, Factory Ramps, Fitness Centers, Hospital Ramps, Hotel Ramps, Inclines, Loading Docks, Office Buildings, Outdoor Walkways, Ramps, School Facilities, Slopes, Superior Anti-Slip Surface, Walkways, Wet Areas, Wheel Chair Accessibility.

**Excellent Traction:** The Ramp Cleat offers the ultimate traction through cleat protrusions, which run the width of the roll. This rubber runner is one of few runner products that offers deep studded barrier for additional toehold when going up inclines or across moist surfaces. The angular corrugations also help remove excess soil from feet when used as an entry scraper mat.

**Permanent Installations:** For most high traffic applications, the Ramp Cleat runner must be permanently installed with a polyurethane based adhesive (such as Chemrex® CX-941).

**Temporary Installations:** For temporary indoor or outdoor installations, the Ramp Cleat rubber runner can be installed with Orcon DS-PS, a double sided sealing tape. By adhering the perimeter of the mat, the semi-permanent 2-sided tape secures the roll for use and allows the flooring to be removed when needed.

**Custom Cuts:** The Ramp-Cleat can be purchased in any length, up to 50 continuous feet, in half-foot increments. Being a sheet good, it can be custom die, laser, or water -jet cut to match any dimension or size required. It could also be easily cut using a sharp utility knife on location, to meet any dimensional requirement.

**Cleaning:** Since this product offers moderate chemical resistance, it can be cleaned with most common household cleaners. Strong, highly caustic cleaning solutions are not recommended. For interior applications, mopping the product is ideal. Exterior, a water hose or broom is the preferred cleaning method.

**Availability:** The Ramp Cleat is always in stock, and will generally ship the same day (allow 24-48 hours for custom cut lengths).

Full Rolls	1-4 rolls	5-19 rolls	20-49 rolls	50+ rolls	In stock
3mm x 36" x 50ft	\$252.00	\$233.10	\$220.50	\$201.60	Yes
Prices above are per roll.					
Custom cut lengths	1-49 feet	50-249 feet	250-999 feet	1000+ feet	In stock
3mm x 36" x Custom Lengths	\$6.50	\$6.29	\$5.95	\$5.44	24-48 hours

\*Prices above are per linear foot. Maximum length is 50 continuous feet on any roll.