

Description: Rolled rubber matting product made from 100% recycled rubber used in a variety of applications. Provides excellent UV protection due to high contents of EPDM, making this matting excellent for indoor and outdoor use. Useful for applications requiring anti-slip, abrasion, and impact protection.

Material: 83% Post-Consumer Recycled Rubber Content

Available Colors: Green Dot, Blue Dot, White Dot, Red Dot, Blue Steel, Candy Corn, and All Black. 1/4" available only in All Black.

Width: 48 inch

Length: 50 ft rolls, Custom lengths up to 50 continuous feet are available upon request.

Thickness: 5mm or 13/64 inch
6.4mm or 1/4 inch
9.5mm or 3/8 inch

Weight: 0.97 lbs/sq ft 5mm
1.25 lbs/sq ft 1/4 inch
2.00 lbs/sq ft 3/8 inch

Origin: Manufactured in the USA

Hardness: 60 Shore A Nominal

Applications: Airports, Animal Care Facilities, Anti-Fatigue Flooring, Art Studios, Assembly Lines, Barns, Baseball Dugouts, Boats, Break Rooms, Clubhouses, Commercial Vehicles, Dance Floors, Daycares, Doggie Day Care, Dog Kennels, Elevators, Farm Facilities, Floor Protection, Garage Flooring, Golf Course, Gyms, Health Clubs, Home Gyms, Hotel Lobbies, Ice Rinks, Industrial Applications, Kid Rooms, Locker Rooms, Movie Sets, Music Studios, Pet Care, Play Areas, Playgrounds, Shelf Lining, Sound Proofing, Spike Protection, Sport Equipment, Stalls, Stock Rooms, Treadmills, Weight Rooms, Yoga.

Unmatched Durability: The Elephant Bark Rubber Flooring is designed to withstand the most abrasive conditions. Made from recycled rubber, it is designed for commercial applications with heavy foot traffic. This product is specifically designed and manufactured for durability.

Resilience: Anti-Fatigue qualities found naturally in rubber are further enhanced by a space age polymer binder used during manufacturing. Each mat is fabricated from thousands of rubber granules and offers superior underfoot comfort and resilience to cushion the shock from running, exercising, walking and standing.

Permanent installations: The Elephant Bark Rubber Flooring can be permanently adhered to a hard subsurface using Chemrex® CX-941 Adhesive.

Density: 60 lb/ft³ or 980 kg/m³.

Elongation: < 145%

Shearing Strength: < 0.60 (N/mm³)

Temperature Stability: -30 C up + 80C in resting condition

Flame Spread: 0.495n/Min., UL standard, (horizontal burning test for classifying material 94HB)

Compression Recovery: Immediate 98.1%
After 24 hours 99.2%
After 48 hours 99.4%
After 72 hours 99.7%
After 96 hours 99.7%, ASTM D575

Tensile Strength: 300 PSI, ASTM D 412

Critical Radiant Flux: 0.11 watts/sq. cm, ASTM E649-94a

Thermal Resistance: 3/4" 0.54 R-Value

Thermal Conductivity: 1.39 K-Value

Tear Resistance: 150ppi, ASTM D624

Elephant Bark

Specifications



NATURAL
RUBBER



RECLAIMED
RUBBER



RECYCLED
RUBBER



SYNTHETIC
RUBBER

January 2011

Temporary Installations: This product is generally heavy enough where its own weight will keep the roll on the ground. A 10ft length of 3/8 inch weighs about 80lbs. In order to keep the edges and entry points from being a trip hazard, Orcon's DS-PS double sided tape can be used for a uniform and level installation.

Indoor/Outdoor: The high content of EPDM, a UV stable elastomer in the Elephant Bark, makes this product an indoor and outdoor mat.

Cleaning: This product can be cleaned using any everyday household cleansers or cleaning implements. Indoor cleaning involves a broom, damp mop, or vacuum cleaner. Outside a water hose, leaf blower, or a broom is sufficient. If desired a mild detergent can be used to sanitize the surface.

Made in the US: This product is completely produced in the United States. Unlike most other matting, it is 100% domestic in nature.

Recycled Product: This product is made from recycled tires. Waste tires!!! Over one quarter of them currently end up in land fills. What better idea could possibly exist than converting these same old spent rubber tires into a surfacing product to beautify your floors!

Custom Cuts: The Elephant-Bark can be purchased in any length, up to 50 continuous feet, in half-foot increments. It is available in a 48 inch width, however, the length is a function of your needs and requirements.

Full Rolls	1-4 rolls	5-19 rolls	20-49 rolls	50+ rolls	In stock
5mm x 48" x 50 ft	\$340.00	\$326.40	\$312.80	\$299.20	Yes
1/4" x 48" x 50 ft	\$375.00	\$360.00	\$345.00	\$330.00	Yes
3/8" x 48" x 50ft	\$600.00	\$576.00	\$552.00	\$528.00	Yes
Prices above are per roll.					
Custom cut lengths	1-49 feet	50-249 feet	250-999 feet	1000+ feet	In stock
5mm x 48" x Custom Lengths	\$8.50	\$7.51	\$7.19	\$6.58	24-48 hours
1/4" x 48" x Custom Lengths	\$10.00	\$8.64	\$7.94	\$7.26	24-48 hours
3/8" x 48" x Custom Lengths	\$16.00	\$12.67	\$12.14	\$11.62	24-48 hours
Prices above are per linear foot. Maximum length is 50 continuous feet on any roll.					