

Elephant Bark

Specifications
November 2008

(Page 1)

<u>Description:</u>	Rolled Rubber Matting product made from 100% recycled rubber used in a variety of applications. Provides excellent UV protection due to high contents of EPDM, making this matting excellent for indoor and outdoor use. Useful for applications requiring anti-slip, abrasion, and impact protection.
<u>Material:</u>	83% Post-Consumer Recycled Rubber Content
<u>Width:</u>	48 inch
<u>Length:</u>	up to 50 ft.
<u>Thickness:</u>	1/4 or 3/8 inch
<u>Weight:</u>	1.25 Lbs./Sq ft 1/4 inch, 2.00 Lbs./Sq ft 3/8 inch
<u>Origin:</u>	Manufactured in the USA
<u>Hardness:</u>	60 Shore A Nominal
<u>Density:</u>	60 lb/ft ³ or 980 kg/m ³ .
<u>Durometer:</u>	65 Shore A, (+/-5)
<u>Elongation:</u>	< 145%
<u>Shearing Strength:</u>	< 0.60 (N/mm ³)
<u>Temperature Stability:</u>	-30 C up + 80C in resting condition
<u>Flame Spread:</u>	0.495 ⁿ /Min., UL standard, (horizontal burning test for classifying material 94HB)
<u>Compression Recovery:</u>	Immediate 98.1% After 24 hours 99.2% After 48 hours 99.4% After 72 hours 99.7% After 96 hours 99.7%, ASTM D575
<u>Tensile Strength:</u>	300 PSI, ASTM D 412
<u>Critical Radiant Flux:</u>	0.11 watts/sq. cm, ASTM E649-94a
<u>Thermal Resistance:</u>	¾" 0.54 R-Value
<u>Thermal Conductivity:</u>	1.39 K-Value
<u>Tear Resistance:</u>	150ppi, ASTM D624
<u>Available Colors:</u>	Green Dot, Blue Dot, White Dot, Red Dot, Blue Steel, Candy Corn, and All Black
<u>Applications:</u>	Athletic Arenas, Art Studios, Anti-Fatigue, Assembly Lines, Barns, Boats, Commercial Fitness Facilities, Doggie Day Care, Elevators, Farm Facilities, Sport Equipment, Floor Protection, Golf Course, Home Gyms, Ice Rinks, In-Line Skating, Industrial Applications, Hallways, Locker Rooms, Pet Care, Runways, Shelving, Spike Protection, Soundproofing, Treadmills, Weight Rooms.
<u>Unmatched Durability:</u>	The Elephant Bark Rubber Flooring is designed to withstand the most abrasive conditions. Made from 100% recycled rubber, it is designed for commercial applications with heavy foot traffic. This product is specifically designed and manufactured for durability.
<u>Resilience:</u>	Anti-Fatigue qualities found naturally in rubber are further enhanced by a space age polymer binder used during manufacturing. Each mat is fabricated from thousands of rubber granules and offers superior underfoot comfort and resilience to cushion the shock from running, exercising, walking and standing.
<u>Permanent installations:</u>	The Elephant Bark Rubber Flooring can be permanently adhered to a hard subsurface using Chemrex® CX-941 Adhesive. The product can be seam sealed to form a water tight surface, which keeps accidents on the surface. Installation instructions can be downloaded above.
<u>Temporary Installations:</u>	This product is generally heavy enough where its own weight will keep the roll on the ground. A 10ft length of 3/8 inch weighs about 80lbs. In order to keep the edges and entry points from being a trip hazard, Orcon's DS-PS double sided tape can be used for a uniform and level installation.
<u>Indoor/Outdoor:</u>	The high content of EPDM, a UV stable elastomer in the Elephant Bark, makes this product an indoor and outdoor mat.
<u>Cleaning:</u>	This product can be cleaned using any everyday household cleansers or cleaning implements. Indoor cleaning involves a broom, damp mop, or vacuum cleaner. Outside a water hose, leaf blower, or a broom is sufficient. If desired a mild detergent can be used to sanitize the surface.

Elephant Bark

Specifications
November 2008
(Page 2)

Made in the US: This product is completely produced in the United States. Unlike most other matting, it is 100% domestic in nature.

Recycled Product: This product is made from recycled tires. Waste tires!!! Over one quarter of them currently end up in land fills. What better idea could possibly exist than converting these same old spent rubber tires into a surfacing product to beautify your floors!

Custom Cuts: The Elephant Bark can be purchased in any length, it is custom cut at no extra charge. It is available in 48 inch widths, however, the length is a function of your needs and requirements.

Availability: Elephant Bark is always in stock and will generally ship within 24 hours.

Price

Thickness x Width x Length

1/4" x 48" x 50ft

Price
\$375.00 per roll. Available in Black or White Dot

Availability
Generally in stock

1/4" x 48" x Any length

\$ 7.50 per linear ft. (custom lengths up to 50ft)

24-48 hour fabrication time

3/8" x 48" x 50ft

\$600.00 per roll. Available in All Black, White Dot, Red Dot, Green Dot, Blue Dot, Candy Corn and Blue Steel.

Generally in stock


3/8" x 48" x Any length

\$ 12.00 per linear ft. (custom lengths up to 50ft)

24-48 hour fabrication time

Specifications and/or prices are subject to change without prior notice.
© 2008 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.
3012 South Croddy Way,
Santa Ana, CA 92704
800-370-9152
714-772-3000
www.rubbercal.com



Rubber Cal