

Gray Sheet

Specifications

January 2011

Description: Gray Sheet is an excellent general purpose gasket material for air, hot and cold water, saturated steam and exterior service.

Compound: Blend of SBR (Styrene Butadiene Rubber) and Natural Rubbers.

Color: Gray

Weight: Approximate weight per square foot: 1/8" weighs 1-1/4 lbs

Durometer: 65-75

Temperature Range: -10 F to 195 F

Minimum Tensile: 435 PSI, 3 MPA

Finish: Smooth

Minimum Elongation: 200%

Gauges: 1/16", 1/8", 3/16", 1/4" (custom gauges up to 2" thick are available upon request)

Widths: 36" & 48" (custom widths up to 78" are available upon request)

Roll Length: 50'

Chemical Resistance: Water, Air, Anti-Freeze, Detergents, Salt Solutions, Bases, Alcohols, and some Acids. It also has a moderate oil and ozone resistance. For Gray Sheet Rubber's compatibility with your specific medium please consult a Rubber-Cal representative.

Applications: Assembly Line Gasketing, Abrasion Resistant Applications, Construction Sites, Cost Conscious Applications, General purpose flapping.

Flexibility: This fairly hard durometer (65-75) sheet rubber offers moderate flexibility and elasticity.

Custom Cuts: In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.

Availability: Popular gauges are always in stock.

Thickness	Width	1.5m to 7.3m or 5' min. to 24'	7.6m to 30.2m or 25' to 99'	30.5m to 152.1m or 100' to 499'	152.4m + or 500' +	In Stock
1/16" or 1.6mm	36" or 91.4 cm	\$4.44	\$3.81	\$3.36	\$2.54	✓
1/8" or 3.2mm	36" or 91.4 cm	\$8.89	\$7.62	\$6.73	\$5.08	✓
3/16" or 4.8mm	36" or 91.4 cm	\$13.33	\$11.43	\$10.09	\$7.62	✓
1/4" or 6.4mm	36" or 91.4 cm	\$17.77	\$15.23	\$13.46	\$10.16	✓

All prices quoted above are per linear foot and in USD\$. Minimum order on any stocked width is 5'.