

## Pure Gum


### Specifications

May 2007

<u>Description:</u>	Pure gum is a tan colored full floating natural rubber. It resists most organic salts, ammonia, acids, and alkalis. It is a non-marking sheet rubber.
<u>Compound:</u>	Natural Rubber
<u>Color:</u>	Tan
<u>Weight:</u>	Approximate weight per square foot: 1/8" weighs 3/4 lb.
<u>Durometer:</u>	35-45
<u>Temperature Range:</u>	-20 F to 170 F
<u>Minimum Tensile:</u>	2,850 PSI
<u>Finish:</u>	Smooth
<u>Minimum Elongation:</u>	600%
<u>Gauges:</u>	1/16", 1/8", 3/16", 1/4", 3/8", 1/2", 3/4", 1"
<u>Widths:</u>	36" and 48" (custom widths and gauges are available upon request)
<u>Roll Length:</u>	25' to 50' (depending on thickness).
<u>Chemical Resistance:</u>	Resists most organic salts, ammonia, acids, and alkalis. For Pure Gum's compatibility with your specific medium please consult a Rubber-Cal representative.
<u>Applications:</u>	Drum Pads, Squeegee Applications, Non-Marking, Some Medical Applications, Professional Window Cleaning.
<u>Flexibility:</u>	This soft durometer (35-45) sheet rubber offers excellent pliability and elasticity.
<u>Custom Cuts:</u>	In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.
<u>Availability:</u>	Always in stock

Rubber-Cal, Inc.  
3012 S. Croddy Way,  
Santa Ana, CA 92704  
800-370-9152

[www.rubbercal.com](http://www.rubbercal.com)



**Rubber**  
**Cal**