

# Shark Tooth Mats


Specifications  
November 2008

<u>Material:</u>	83% Post-Consumer Recycled Rubber Content
<u>Size:</u>	4ft. x 6ft., 3ft. x 4ft., 2ft. x 3ft.
<u>Thickness:</u>	3/4 inch
<u>Color:</u>	Black
<u>Weight:</u>	4.0 Lbs./Sqr ft 3/4 inch
<u>Surface:</u>	Flat on one side, Mesh texture (anti-skid) on the reverse.
<u>Origin:</u>	Manufactured in the USA
<u>Hardness:</u>	60 Shore A Nominal, ASTM D2240
<u>Tensile Strength:</u>	Minimum 300 psi
<u>Density:</u>	60 LBS/FT <sup>3</sup> , ASTM D 3676
<u>Ultimate Elongation:</u>	83% Minimum, ASTM D 412
<u>Flame Spread:</u>	0.485 Min., UL 94 Standard
<u>Critical Radiant Flux:</u>	0.11 watts/sq. cm, ASTM E649-94a
<u>Thermal Resistance:</u>	¾" 0.54 R-Value
<u>Thermal Conductivity:</u>	1.39 K-Value
<u>Tear Resistance:</u>	150ppi, ASTM D624
<u>Compression &amp; Recovery:</u>	Immediate 98.1% After 24 hours 99.2% After 48 hours 99.4% After 72 hours 99.7% After 96 hours 99.7%, ASTM D575
<u>Applications:</u>	Weight Rooms, Ice Rinks, Golf Course, Laundry Rooms, Pothole Reduction, Pet Care, Ski Lodges, Boat Decks, Assembly Lines, Locker Rooms, Spike Protection, Industrial Applications, Home Gyms, Cardio Decks, Floor Protection, Anti-Fatigue, Heavy Duty Outdoor Application.
<u>Unmatched Durability:</u>	The Shark Tooth mats can protect floors from damage usually caused by the impact from dropping barbells, industrial equipment, or protect the equipment from an inhospitable concrete floor. The rubber mats have cushioning features that protect parts and sub-floors from dings, scuffs, and other damage. The 3/4 inch thick rubber provides superior wear life compared to thinner, light-duty matting.
<u>Resilience:</u>	Anti-Fatigue qualities found naturally in rubber are further enhanced by a space age polymer binder used during manufacturing. Each mat is fabricated from thousands of rubber granules and offers superior underfoot comfort and resilience.
<u>Installation:</u>	The Shark Tooth is a mat and is recommended for installation in spots rather than as a flooring product. Permanent installation of this product is not necessary, since the weight of the mat (100 lbs. in a 4ft x 6ft) is usually more than sufficient of keep the product in place. Therefore, the product remains portable, and may be moved or rearranged whenever necessary.
<u>Indoor / Outdoor:</u>	The high content of EPDM, which is a UV stable elastomer in the Shark Tooth, makes the product an indoor and outdoor mat.
<u>Cleaning:</u>	This product can be cleaned using any everyday household cleansers or cleaning implements. Indoor cleaning involves a broom, damp mop, or a vacuum cleaner. Outside, a water hose, leaf blower or broom is sufficient. If desired a mild detergent can be used to sanitize the surface.
<u>Made in the USA:</u>	This product is completely produced in the United States. Unlike most other matting, it is 100% domestic in nature.
<u>Recycled Product:</u>	Made from 100% recycled California tires, which helps reduce stockpiles. Millions of car tires are discarded each year. These tire stockpiles are susceptible to fires that cause tremendous air pollution. Also, used tires accumulate water and become breeding ground for mosquitoes. The Shark Tooth is a <u>Green</u> Product.
<u>Availability:</u>	The Shark Tooth is always in stock, and will generally ship same day ordered.

<u>Price</u>	<u>Availability</u>
<u>Thickness x Width x Length</u>	
3/4" x 4ft x 6ft.	Generally in stock
3/4" x 3ft x 4ft.	Generally in stock
3/4" x 2ft x 3ft.	Generally in stock

Specifications and/or prices are subject to change without prior notice.  
© 2008 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.  
3012 South Croddy Way,  
Santa Ana, CA 92704  
800-370-9152  
714-772-3000  
[www.rubbercal.com](http://www.rubbercal.com)



# Rubber Cal