


# Armor-Lock (Fitness)

Specifications

August 2021

<u>Description:</u>	These durable and solid interlocking rubber tiles are idea for any workout area. This 8-millimeter rubber tile is idea for those home gyms that require a high-performing heavy-duty surface. Smaller and lighter than the Armor Lock (Fitness), this product is easier to handle, which make it a very friendly “Do-It-Yourself” project. Armor Lock (Fitness) Tile is well suited for applications that require commercial grade floor protection at more affordable rate.
<u>Materials:</u>	Natural and Reclaimed Rubber
<u>Thickness:</u>	8mm (just under 3/8-inch thick)
<u>Tile Sizes:</u>	20-inches by 20-inches (approximate)
<u>Weight:</u>	5.5lbs
<u>Available Color:</u>	Black
<u>Applications:</u>	Basement Floors, Commercial Gyms, Competition Centers, Dance Rooms, DIY Floors, Factories, Fitness Centers, Garage Floors, Gym Equipment Mats, Heavy-Duty Flooring, Home Gyms, Interlocking Tile Floors, Locker Rooms, Manufacturing Floors, Martial Arts Studios, Modular Floors, Pet Groomer Stations, Pool Decks, Residential Gyms, Safety Surface Matting, Sporting Centers, Sports Matting, Traction Tiles, Work Areas, Workout Ares.
<u>Moisture Resistance:</u>	Unlike a fabric mat, which absorbs and harbors the growth of mold, mildew, and bacteria, a rubberized surface provides a hostile environment these sorts of microbes. This is an especially useful quality in applications that see any amount of moisture. A gym is exposed to sweat, and therefore should be cleaned regularly. The use of water or mild detergents will not affect the functionality of this product.
<u>Easy Installation:</u>	These interlocking tiles require no use of adhesives for installation.
<u>Eco-Tiles!</u>	The rubber recycling process begins with shredding. After the steel and reinforcing fibers are removed, and the material is put through a second round of grinding, the resulting rubber powder is ready for remanufacturing. Up until this point, this inert material could only be used in applications that do not require vulcanization. In the rubber recycling process, devulcanization begins with delinking of the sulfur molecules from the rubber molecules, facilitating the formation of new cross-linkages. Reclaimed rubber is the de-vulcanized product of recycled tire crumb!
<u>Ideal for Gyms:</u>	These tiles are great for shock absorbance and drowning out the noise caused by vibrating equipment and dropped weights. Their durability will allow them to last for years and years without affecting their performance. They are also an excellent protective buffer between hard flooring and expensive weight room equipment.
<u>Cleaning:</u>	This product can be easily cleaned with water and common detergents. Mop or sweep as necessary with no harm to performance. This tile is completely water-resistant and cannot be harmed due to moisture.
<u>Availability:</u>	Armor Lock (Fitness) is always in stock and will generally ship within 24 hours.
<u>California Prop 65:</u>	 <b>WARNING:</b> Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .



# Rubber Cal

Specifications and/or prices are subject to change without prior notice.

© 2021 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.

18424 Mt Langley St,

Fountain Valley, CA 92708

800-370-9152

[www.rubbercal.com](http://www.rubbercal.com)