

# Closed Cell Rubber - Blend

Specifications

August 2021

Description:

General purpose closed cell sponge made from SBR rubber available in sheet form. Ideal for outdoor or indoor use in shock absorption and gasket related applications.

Compound:

A Blend of CR & SBR

Color:

Black

Sheet Size:

39" x 78" (1000\*2000mm), Tolerances +20mm or +0.75"

Gauges:

1/16", 3/32", 1/8", 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", 3/4", 1"

Temperature Range:

-40 C to +95C , -40 F to +200F

Shore Hardness:

20-25 Shore C

Density Average:

150kgs/m<sup>3</sup> +/- 20kgs/m<sup>3</sup>

Water Absorption:

3% (<5%)

Ultimate Elongation:

216%

Tensile Strength:

1.03Mpa

PSA:

Pressure sensitive adhesive can be applied to this product upon request.

Custom Cuts:

In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.


Availability:


This product is generally stocked and can ship within 24 hours.

Minimum Order:

One Sheet, volume discounts are available at 5, 25 and 50 units

California Prop 65:

 **WARNING:** Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



# Rubber Cal

Specifications and/or prices are subject to change without prior notice.

© 2021 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.

18424 Mt Langley St,

Fountain Valley, CA 92708

1-844-Rubber-4

[www.rubbercal.com](http://www.rubbercal.com)