



# Cloth Inserted SBR - 70A

Specifications  
August 2021

<u>Description:</u>	Cloth inserted sheet materials are designed to add stability when mechanical fastening is necessary. Cloth Inserted SBR is stocked.
<u>Compound:</u>	Standard sheet is a made of SBR (Styrene Butadiene Rubber) with a polyester inserted fabric
<u>Color:</u>	Black
<u>Weight:</u>	Approximate weight per square foot: 1/8" weighs 1lbs.
<u>Durometer:</u>	70 Shore A, +/- 5
<u>Temperature Range:</u>	-10 F to 190 F
<u>Minimum Tensile:</u>	500 PSI or 4 MPA
<u>Finish:</u>	Smooth
<u>Minimum Elongation:</u>	200%
<u>Gauges:</u>	1/16" 1ply, 1/8" 2plies, 3/16" 3plies, 1/4" 3plies.
<u>Widths:</u>	10", 36" and 48" (custom widths and gauges are available upon request)
<u>Roll Length:</u>	50'
<u>Applications:</u>	For use where mechanical fastening is necessary.
<u>PSA:</u>	Pressure sensitive adhesive can be applied to this product upon request.
<u>Flexibility:</u>	This hard durometer (65-75) sheet rubber offers limited flexibility and low elasticity.
<u>Custom Cuts:</u>	In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.
<u>Availability:</u>	CI SBR is generally in stock.
<u>California Prop 65:</u>	 <b>WARNING:</b> Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .



# Rubber Cal

Specifications and/or prices are subject to change without prior notice.  
© 2021 Rubber-Cal all rights reserved.  
Rubber-Cal, Inc.  
18424 Mt Langley St,  
Fountain Valley, CA 92708  
800-370-9152  
[www.rubbercal.com](http://www.rubbercal.com)