EPDM - Commercial Grade - 60A

Specifications August 2021

Description: Ethylene Propylene Diene Monomer (EPDM) and SBR blended sheet is a

black colored sheet rubber which provides very good resistance to

weathering, ozone and UV exposure.

Compound: 10% Ethylene Propylene Diene Monomer (EPDM) Base, SBR

Color: Black

Weight: Approximate weight per square foot: 1/8" weighs 1-1/4 lbs.

<u>Durometer:</u> 60 Shore A, +/- 5 <u>Temperature Range:</u> -40 F to 212 F <u>Minimum Tensile:</u> 725 PSI or 5 MPA

<u>Finish:</u> Smooth Minimum Elongation: 300%

Gauges: 1/16", 3/32", 1/8", 3/16", 1/4", 3/8", 1/2" (custom gauges up to 2" thick are

available upon request)

Widths: 36" (custom widths up to 78" are available upon request)

Roll Length: 25' or 50' depending on thickness.

Pressure sensitive adhesive can be applied to this product upon request.

Chemical Resistance:

Good resistance to UV rays and ozone. Good resistance to Anti-freeze,
Synthetic Detergents, Acetone, Boric acid, Ethanol, Formaldehyde, Mercury,
Potassium Sulfate, Silver Nitrate, Steam (up to 212 Fahrenheit), Saccharin.

For EPDM Blend's compatibility with your specific medium please consult a Rubber-Cal representative.

Rubber-Cai representative

<u>Applications:</u> Provides outstanding resistance to weathering, ozone and UV exposure.

Gasket, bumper and general exterior applications.

<u>Flexibility:</u> This medium durometer (55-65) sheet rubber offers good pliability and

elasticity.

<u>Custom Cuts:</u> In addition to hand fabrication, this product can be fabricated using laser,

die, and water-jet cut. Please submit your drawings for a price quote.

<u>Availability:</u> Popular gauges are generally in stock.

www.P65Warnings.ca.gov.



Specifications and/or prices are subject to change without prior notice. © 2021 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.

18424 Mt Langley St,
Fountain Valley, CA 92708

800-370-9152

www.rubbercal.com