Heavy Black Conveyor Belt

Specifications August 2021

<u>Description:</u> Heavy Conveyor Belt is a rubber product compounded to provide optimal

abrasion resistance and flex life for abrasion and impact absorption applications. The high-tension synthetic fabric insert results in minimum stretch, full resistance to mildew and rot, and maximum mechanical fastener holding ability and impact resistance, and highest adhesion between plies

and covers.

Compound: SBR (Styrene Butadiene Rubber)

Color: Black

Weight: 2ply 2lbs. per square ft., 3ply 3lbs. per square ft.

<u>Durometer:</u> 75 Shore A, +/- 5 <u>Temperature Range:</u> -20 F to 200 F Minimum Tensile: 2175 PSI or 15MPA

Finish: Smooth
Construction: 2ply and 3ply

Thickness: 2ply 0.30" or 7.5mm, 3ply 0.41" or 10.5mm

<u>Widths:</u> 3", 4" 6" & 38" inch (3ply) – 4", 6", 8", 10" 12" & 40" (2ply)

Custom widths up to 40" available upon request.

Roll Length: Up to 500 feet continuous.

<u>Chemical Resistance:</u> Excellent resistance to Hydrogen Gas, Natural Gas, Salt/Sea Water, Butanol

(primary), Silicone Oils and Greases, and many more. Moderate oil,

petroleum-based solvents and ozone resistance.

<u>Applications:</u> Cement, Cushion Pad, Elevators, Fertilizers, Grains, Hot Asphalt, Mining,

Minerals, Primary and Secondary Crushers, Sand and Gravel, Skirting, Take

Away Conveyors, Wood Chips

<u>Abrasion Resistance:</u> The combination of high quality rubber compounds, synthetic plies of fabric

and high tensile strength culminate in a top quality durable rubber product.

This product can be custom cut to any specific dimension.

Availability: Always in stock

Custom Cuts:

California Prop 65: WARNING: Cancer and Reproductive Harm -

www.P65Warnings.ca.gov.



Specifications and/or prices are subject to change without prior notice. © 2021 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.
18424 Mt Langley St,
Fountain Valley, CA 92708
800-370-9152
www.rubbercal.com