
Neoprene - Commercial Grade - 60A Specifications August 2021

Description:	Neoprene sheet is a black colored rubber which is used where moderate oil, petroleum, ozone and weathering-resistance is needed. It is very popular due to the broad range of applications in which it may be used.
Compound:	10% Neoprene Base, Blend of SBR (Styrene Butadiene Rubber) and CR (Neoprene).
<u>Color:</u>	Black
Weight:	Approximate weight per square foot: 1/8" weighs 1-1/4 lbs.
Durometer:	60 Shore A, +/- 5
Temperature Range:	-20 F to 212 F
Minimum Tensile:	725 PSI or 5 MPA
<u>Finish:</u>	Smooth
Minimum Elongation:	300%
Gauges:	1/32", 1/16", 3/32", 1/8", 3/16", 1/4", 3/8", 1/2", 3/4", 1" (custom gauges up
	to 2" thick are available upon request)
Widths:	36" and 48" (custom widths up to 78" are available upon request)
Roll Length:	25' or 50' (depending on thickness)
<u>PSA:</u>	Pressure sensitive adhesive can be applied to this product upon request.
Chemical Resistance:	Excellent resistance to Hydrogen Gas, Natural Gas, Salt/Sea Water, Butanol
	(primary), Acetic Acids (up to 20%), Ammonium Salts, Mineral Oils,
	Silicone Oils and Greases, and many more. Moderate oil, petroleum-based
	solvents and ozone resistance. For Neoprene's compatibility with your
	specific medium please consult a Rubber-Cal representative.
Applications:	Sound Studios, Construction Sites, Industrial Gasketing, Underlayment,
	Chemical Resistant Applications, Laboratory Equipment Protection, Marine.
<u>Flexibility:</u>	This medium durometer (55-65) sheet rubber offers moderate pliability and
	elasticity.
Custom Cuts:	In addition to hand fabrication, this product can be fabricated using laser,
	die, and water-jet cut. Please submit your drawings for a price quote.
Availability:	Most gauges and widths are in stock.
<u>California Prop 65:</u>	WARNING: Cancer and Reproductive Harm -
	www.P65Warnings.ca.gov.





Specifications and/or prices are subject to change without prior notice. © 2021 Rubber-Cal all rights reserved. Rubber-Cal, Inc. 18424 Mt Langley St, Fountain Valley, CA 92708 800-370-9152 www.rubbercal.com