

# Open Cell Rubber - EPDM

Specifications

August 2021

Description:

General purpose open cell sponge made from EPDM rubber available in sheet form. Ideal for outdoor or indoor use in shock absorption and gasket related applications.

Compound:

EPDM rubber (ethylene propylene diene monomer rubber)

Color:

Black

Sheet Size:

39" x 78" (1000\*2000mm), Tolerances +20mm or +0.75"

Gauges:

1/8", 1/4", 3/8", 1/2", 3/4", 1"

Temperature Range:

-40 F to 160 F

Finish:

Textured and the cellular feature visible on the surface

Elongation:

168% - GB/T 6344-1996

Compression Strength:

1.56 kPA per ASTM D695-15

Tensile Strength:

0.10 MPA - JIS K6767:1999

Density:

0.92 Grams/CM2 - GB/T 6343-1995

PSA:

Pressure sensitive adhesive can be applied to this product upon request.


Custom Cuts:


In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.

Availability:

This product is generally stocked and can ship within 24 hours.

California Prop 65:

 **WARNING:** Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



# Rubber Cal

Specifications and/or prices are subject to change without prior notice.

© 2021 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.

18424 Mt Langley St,

Fountain Valley, CA 92708

800-370-9152

[www.rubbercal.com](http://www.rubbercal.com)