



SBR - Gray - 65A

Specifications

August 2021

<u>Description:</u>	Gray Sheet is an excellent general purpose gasket material for air, hot and cold water, saturated steam and exterior service.
<u>Compound:</u>	Blend of SBR (Styrene Butadiene Rubber) and Natural Rubbers.
<u>Color:</u>	Gray
<u>Weight:</u>	Approximate weight per square foot: 1/8" weighs 1-1/4 lbs
<u>Durometer:</u>	65 Shore A, +/- 5
<u>Temperature Range:</u>	-10 F to 195 F
<u>Minimum Tensile:</u>	435 PSI, 3 MPA
<u>Finish:</u>	Smooth
<u>Minimum Elongation:</u>	300%
<u>Gauges:</u>	1/16", 1/8", 3/16", 1/4" (custom gauges up to 2" thick are available upon request)
<u>Widths:</u>	36" (custom widths up to 78" are available upon request)
<u>Roll Length:</u>	50'
<u>PSA:</u>	Pressure sensitive adhesive can be applied to this product upon request.
<u>Chemical Resistance:</u>	Water, Air, Anti-Freeze, Detergents, Salt Solutions, Bases, Alcohols, and some Acids. It also has a moderate oil and ozone resistance. For Gray Sheet Rubber's compatibility with your specific medium please consult a Rubber-Cal representative.
<u>Applications:</u>	Assembly Line Gasketing, Abrasion Resistant Applications, Construction Sites, Cost Conscious Applications, General purpose flapping.
<u>Flexibility:</u>	This fairly hard durometer (60-70) sheet rubber offers moderate flexibility and elasticity.
<u>Custom Cuts:</u>	In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.
<u>Availability:</u>	Popular gauges are always in stock.
<u>California Prop 65:</u>	 WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov .



Rubber Cal

Specifications and/or prices are subject to change without prior notice.

© 2021 Rubber-Cal all rights reserved.

Rubber-Cal, Inc.

18424 Mt Langley St.

Fountain Valley, CA 92708

800-370-9152

www.rubbercal.com