



# SBR - Red - 65A

Specifications  
August 2021

<u>Description:</u>	Red Sheet is an excellent general-purpose gasket material for air, hot and cold water, saturated steam and exterior service.
<u>Compound:</u>	Blend of SBR (Styrene Butadiene Rubber) and Natural Rubbers.
<u>Color:</u>	Red
<u>Weight:</u>	Approximate weight per square foot: 1/8" weighs 1-1/4 lbs.
<u>Durometer:</u>	65 Shore A, +/- 5
<u>Temperature Range:</u>	-10 F to 195 F
<u>Minimum Tensile:</u>	435 PSI, 3 MPA
<u>Finish:</u>	Smooth
<u>Minimum Elongation:</u>	300%
<u>Gauges:</u>	1/16", 1/8", 3/16", 1/4" (custom gauges up to 2" thick are available upon request)
<u>Widths:</u>	36" or 48" (custom widths up to 78" are available upon request)
<u>Roll Length:</u>	50'
<u>PSA:</u>	Pressure sensitive adhesive can be applied to this product upon request.
<u>Chemical Resistance:</u>	Water, Air, Anti-Freeze, Detergents, Salt Solutions, Bases, Alcohols, and some Acids. It also has a moderate oil and ozone resistance. For Red Sheet Rubber's compatibility with your specific medium please consult a Rubber-Cal representative.
<u>Applications:</u>	Assembly Line Gasketing, Abrasion Resistant Applications, Construction Sites, Cost Conscious Applications, General purpose flapping.
<u>Flexibility:</u>	This fairly hard durometer (65-75) sheet rubber offers moderate flexibility and minimal elasticity.
<u>Custom Cuts:</u>	In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.
<u>Availability:</u>	Popular gauges are always in stock.
<u>California Prop 65:</u>	 <b>WARNING:</b> Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .



# Rubber Cal

Specifications and/or prices are subject to change without prior notice.  
© 2021 Rubber-Cal all rights reserved.  
Rubber-Cal, Inc.  
18424 Mt Langley St,  
Fountain Valley, CA 92708  
800-370-9152  
[www.rubbercal.com](http://www.rubbercal.com)