Skirtboard - SBR Rubber - 70A

Specifications August 2021

<u>Description:</u> Skirtboard is a sturdy sheet product designed for use as conveyor skirtboard

or belt wiper.

<u>Compound:</u> SBR <u>Color:</u> Black

Weight: Approximate weight per square foot: 1/8" weighs 1 lb.

<u>Durometer:</u> 65-75

Temperature Range: -10 F to 190 F Minimum Tensile: 725 PSI or 5 MPA

<u>Finish:</u> Smooth <u>Minimum Elongation:</u> 300%

Gauges: 1/8", 1/4", 3/8", 1/2", 3/4", 1", 1.5" (custom gauges up to 2" thick are

available upon request)

1/8" to 1/2" are sold in 25 and 50ft. lengths only.

Widths: 4", 6", 8", 10", 12", 36", 48" (custom widths up to 78" are available upon

request)

Roll Length: 25 or 50ft.

<u>Chemical Resistance:</u> Good resistance to Ethanol, Formaldehyde, Glycerin, Sea Water, Boric

Acid, and Chlorine Solutions. Not suited for use with Oils, Fuels, Solvents, or Hydraulic Fluids. For Skirtboard's compatibility with your specific

medium please consult a Rubber-Cal representative.

<u>Applications:</u> Street Sweepers, Abrasion Resistant Applications, Snowplow Blades,

Airfield Applications, General Industrial Padding and Gasketing

<u>Flexibility:</u> This hard durometer (65-75) sheet rubber offers limited pliability and

elasticity.

<u>Custom Cuts:</u> In addition to hand fabrication, this product can be fabricated using laser,

die, and water-jet cut. Please submit your drawings for a price quote.

Availability: Popular gauges and widths and stock.

www.P65Warnings.ca.gov.



Specifications and/or prices are subject to change without prior notice.

© 2021 Rubber-Cal all rights reserved.
Rubber-Cal, Inc.
18424 Mt Langley St,
Fountain Valley, CA 92708
800-370-9152
www.rubbercal.com