X-Derm - Textured Recycled Rubber - 60A Specifications August 2021

Description:	The X-Derm's unique coarse and bumpy surface in addition to its resilient texture offer unequal aesthetic appeal for industrial and commercial
	applications.
Compound:	Made from recycled rubber products
Color:	Black
Weight:	Approximate weight per square foot: 0.4 lbs.
Durometer:	55-65
Temperature Range:	-20 F to 170 F
Minimum Tensile:	MPA 3 or 435 PSI, ASTM-D412-97 Method A, Die C
Finish:	Pebble-Top
Minimum Elongation:	218%, ASTM-D412-97 Method A, Die C
Gauge:	0.060", 60 Mil (custom gauges up to $\frac{1}{2}$ " available upon request)
Widths:	36" and 48" Standard in stock (custom widths up to 60 inch are available
	upon request)
PSA:	Avery Dennison HB 3081-53 series pressure sensitive adhesive
Roll Length:	100' (custom length available upon request)
Weather Resistance:	100%, ASTM-D1171
Staining Resistance:	No visible migration, ASTM-D925, Method B
Flexibility:	This average durometer (55-65) sheet rubber offers good flexibility and good
	elasticity.
Flammability:	1.19 in/min, ASTM-FMVSS-302
Availability:	Generally in stock.
Special Feature:	Pressure Sensitive Adhesive (PSA) available upon request.
Custom Cuts:	In addition to hand fabrication, this product can be fabricated using laser,
	die, and water-jet cut. Please submit your drawings for a price quote.
Applications:	Traction mat, Sure-Foot Surface, Weather Resistant, Outdoor Use, Ozone
	Proof, Mechanical Sports Equipment, Pedals, Steps, Farm Machinery,
	Construction Equipment, Aerobic Equipment, Equipment Storage, Industrial
	Liners, Boat Runners, Walkways, Alley Mats, Industrial Shelves, Textured
	Walls, Soundproofing, Chair Mats, Delivery Vehicle Liners, Pet Care Liners
California Prop 65:	WARNING: Cancer and Reproductive Harm -
	www.P65Warnings.ca.gov.



Specifications and/or prices are subject to change without prior notice. @ 2021 Rubber-Cal all rights reserved. Rubber-Cal, Inc. 18424 Mt Langley St, Fountain Valley, CA 92708 800-370-9152 www.rubbercal.com